

TECHNICAL DATA

MEASUREMENTS	30- 2
ENGINE	30- 2
LUBRICATION SYSTEM	30- 3
COOLING SYSTEM	30- 3
FUEL SYSTEM	30- 4
ENGINE ELECTRICAL SYSTEM	30- 4
CLUTCH	30- 6
MANUAL TRANSMISSION	30- 6
AUTOMATIC TRANSMISSION	30- 6
PROPELLER SHAFT	30- 8
REAR AXLE	30- 8
MANUAL STEERING	30- 8
POWER STEERING	30- 8
BRAKES	30- 9
WHEELS AND TIRES	30- 9
SUSPENSION	30-10
BODY ELECTRICAL SYSTEM	30-10

MEASUREMENTS			
Overall length	4,285 mm (169 in)	Apex seal	
Overall width		Length	
(Without side protector)	1,650 mm (65 in)	12A Engine	69.8 mm (2.7481 in)
(With side protector)	1,675 mm (66 in)	13B Engine	79.8 mm (3.1418 in)
Overall height	1,260 mm (50 in)	Width	3.0 mm (0.1181 in)
Distance between wheel center and fender line		Height	
Front	364 ± 20 mm (14.3 ± 0.8 in)	Standard	8.5 mm (0.3347 in)
Rear	358 ± 20 mm (14.0 ± 0.8 in)	Limit	7.0 mm (0.2756 in)
Wheel base	2,420 mm (95 in)	Clearance of apex seal and rotor groove (ΔG)	
Tread		Standard	0.05 ~ 0.09 mm (0.0020 ~ 0.0035 in)
Front	1,420 mm (56 in)	Limit	0.15 mm (0.0059 in)
Rear	1,400 mm (55 in)	Apex seal spring	
Minimum road clearance	160 mm (6 in)	Free height	
Minimum turning radius	4.8 m (15 ft 9 in)	Standard	
		12A Engine	6.9 mm (0.2717 in) or more
		13B Engine	5.7 mm (0.2244 in) or more
		Limit	
		12A Engine	5.5 mm (0.2165 in)
		13B Engine	3.8 mm (0.1496 in)
1. ENGINE		Side seal	
Displacement		Thickness	1.0 mm (0.0394 in)
12A Engine	573 CC (35.0 cu-in) X 2 rotors	Height	3.5 mm (0.1378 in)
13B Engine	654 CC (40.0 cu-in) X 2 rotors	Clearance of side seal and rotor groove (ΔW)	
Compression ratio	9.4 : 1	Standard	0.03 ~ 0.08 mm (0.0012 ~ 0.0031 in)
Compression pressure	600 kpa (85 lb/in ²)	Limit	0.10 mm (0.0039 in)
Limit	at 250 rpm	Clearance of side seal and corner seal (ΔE)	
Max. permissible difference between chambers	150 kpa (21 lb/in ²)	Standard	0.05 ~ 0.15 mm (0.0020 ~ 0.0059 in)
Port timing		Limit	0.40 mm (0.0157 in)
12A Engine		Side seal protrusion	More than 0.5 mm (0.0197 in)
Intake opens ATDC	32°	Oil seal	
Intake closes ABDC	40°	Height	5.6 mm (0.2205 in)
Exhaust opens BBDC	75°	Contact width of oil seal lip	Less than 0.5 mm (0.0197 in)
Exhaust closes ATDC	38°	Oil seal protrusion	More than 0.5 mm (0.0197 in)
13B Engine		Corner seal	
Intake opens ATDC	32°(Pr.) 32°(Sec.) 45° (Auxiliary)	Outer diameter	11.0 mm (0.4331 in)
Intake closes ABDC	40°(Pr.) 30°(Sec.) 70° (Auxiliary)	Height	7.0 mm (0.2756 in)
Exhaust opens BBDC	71°	Corner seal protrusion	More than 0.5 mm (0.0197 in)
Exhaust closes ATDC	48°	Main bearing clearance	
Side housings (Front, intermediate and rear housings)		Standard	0.04 ~ 0.08 mm (0.0016 ~ 0.0031 in)
Width standard		Wear limit	0.10 mm (0.0039 in)
Front	40 mm (1.5748 in)	Rotor bearing clearance	
Intermediate	50 mm (1.9685 in)	Standard	0.04 ~ 0.08 mm (0.0016 ~ 0.0031 in)
Rear	60 mm (2.3622 in)	Wear limit	0.10 mm (0.0039 in)
Limit of distortion	0.04 mm (0.0016 in)	Eccentric shaft	
Limit of wear		Eccentricity of rotor journal	15.0 mm (0.5906 in)
Sliding surface	0.10 mm (0.0039 in)	Main journal diameter	43 mm (1.6929 in)
Rotor housing		Rotor journal diameter	74 mm (2.9134 in)
Width		Max. permissible run-out	0.06 mm (0.0024 in)
12A Engine	70.0 mm (2.7559 in)	End play	
13B Engine	80.0 mm (3.1497 in)	Standard	0.04 ~ 0.07 mm (0.0016 ~ 0.0028 in)
Max. permissible difference in width	0.06 mm (0.0024 in)	Limit	0.09 mm (0.0035 in)
Rotor			
Width			
12A Engine	69.8 mm (2.7481 in)		
13B Engine	79.85 mm (3.1438 in)		
Clearance of side housing and rotor (ΔR)			
Standard			
12A Engine	0.12 ~ 0.19 mm (0.0047 ~ 0.0075 in)		
13B Engine	0.12 ~ 0.21 mm (0.0047 ~ 0.0083 in)		
Limit	0.10 mm (0.0039 in)		

Alternator belt tension (slack) (Between alternator and eccentric shaft pulley) Belt deflection Air pump belt tension (slack) (Between air pump and water pump pulley) Belt deflection	15 ± 2 mm (0.5906 ± 0.0787 in) 12 ± 1 mm (0.4724 ± 0.0394 in)	Oil metering pump Feeding capacity of 2,000 rpm of engine 12A Engine 13B Engine	1.8 ~ 2.2 cc/6 min. (0.110 ~ 0.134 U.S. cu-in/6 min.) 0.8 ~ 1.2 cc/6 min. (0.049 ~ 0.073 U.S. cu-in/6 min.)
TIGHTENING TORQUE			
	N-m	ft-lb	
Oil pump sprocket	32 ~ 47	23 ~ 34	
Dil pan	8 ~ 11	6 ~ 8	
Inlet manifold	19 ~ 26	14 ~ 19	
Exhaust manifold	32 ~ 47	23 ~ 34	
Spark plugs	13 ~ 18	9 ~ 11	
Eccentric shaft pulley	100 ~ 120	72 ~ 87	
Temperature gauge unit	7 ~ 8	5 ~ 6	
Tension bolts	32 ~ 38	23 ~ 27	
Water temperature switch	35 ~ 45	25 ~ 33	
Lubricant Classification Above -10°C (15°F) -25°C ~ 30°C (-13°F ~ 86°F) Above -25°C (-13°F) Below -20°C (-4°F) Below 0°C (32°F)			
Oil capacity Full capacity 12A Engine 4.6 liters (4.9 U.S. quarts) 13B Engine 5.8 liters (6.1 U.S. quarts)			
Oil pan capacity 12A Engine 4.2 liters (4.4 U.S. quarts) 13B Engine 4.6 liters (4.9 U.S. quarts)			
2. LUBRICATING SYSTEM			
Oil pump Type Feeding capacity at 1,000 rpm of engine Oil pump driven by Limit of chain slack Outer rotor and body Clearance Standard Wear limit Clearance between rotor lobes Standard Wear limit Rotor end float Standard Wear limit Oil pressure at 3,000 rpm of engine Oil pressure at idle speed of engine ("D" range for automatic) Pressure regulator valve (Rear housing) Operating pressure Free length of spring Pressure control valve (Front cover) Operating pressure Free length of spring By-pass valve (Oil cooler) Opening pressure Oil filter Type Relief valve opens at	Rotor 7.0 liters/min. (7.4 U.S. quarts/min.) (6.2 Imp. quarts/min.) Chain and sprocket 12 mm (0.4724 in) 0.20 ~ 0.25 mm (0.0079 ~ 0.0098 in) 0.30 mm (0.0118 in) 0.01 ~ 0.09 mm (0.0004 ~ 0.0035 in) 0.15 mm (0.0059 in) 0.03 ~ 0.13 mm (0.0012 ~ 0.0051 in) 0.15 mm (0.0059 in) 450 ~ 550 kpa (64.0 ~ 78.2 lb/in ²) 90 ~ 270 kpa (12.8 ~ 38.4 lb/in ²) 500 kpa (71.1 lb/in ²) at 3,000 rpm of engine 46.4 mm (1.8268 in) 800 kpa (113.8 lb/in ²) 69.6 mm (2.7402 in) 300 kpa at 60°C (42.7 lb/in ² at 140°F)	TIGHTENING TORQUE	
		N-m	ft-lb
Oil pump sprocket		32 ~ 47	23 ~ 34
Oil pan		8 ~ 11	6 ~ 8
3. COOLING SYSTEM			
Water pump Type Feeding capacity at 6,500 rpm of engine Pump driven by Pulley ratio of eccentric shaft and pump Fan Fan diameter Number of fan blades Fan drive Standard revolution of fan Thermostat 1 type Starts to open Fully opens at Lift Radiator Type Pressure cap opens at Cooling capacity With heater Without heater	Centrifugal impeller 150 ~ 160 liters/min (39.6 ~ 42.3 U.S. gal/min.) (33.0 ~ 35.2 Imp. gal/min.) "V" belt 1 : 1.18 390 mm (15.3546 in) 8 Less than 900 rpm at 3400 rpm of engine Wax pellet 82 ± 1.5°C (180 ± 2.7°F) 95°C (203°F) 8 ~ 10 mm (0.3150 ~ 0.3937 in) Corrugated fin, with expansion tank 90 ~ 15 kpa (12.8 ± 2.0 lb/in ²) 9.5 liters (10 U.S. quarts) (8.4 Imp. quarts) 8.5 liters (9.0 U.S. quarts) (7.5 Imp. quarts)		

TIGHTENING TORQUE				
	N-m	ft-lb		
Temperature gauge unit	7 ~ 8	5 ~ 6	13B Engine Air cleaner element Sub-zero starting assist fluid Long life dry Anti-freeze 90% Water 10%	
Water temperature switch	35 ~ 45	25 ~ 33		
Water pump	18 ~ 27	13 ~ 20		
4. FUEL SYSTEM				
12A Engine				
Fuel tank capacity	63 liters (16.4 U.S. gal.) (13.9 Imp. gal.)		Fuel tank capacity 63 liters (16.4 U.S. gal.) (13.9 Imp. gal.)	
Fuel pump	Motor		Fuel pump Type Motor	
Type	20 ~ 25 kpa (2.84 ~ 3.55 lb/in ²)		Outlet pressure 350 ~ 500 kpa (49.8 ~ 71.1 lb/in ²)	
Outlet pressure	More than 1,400 cc/min. (1.48 U.S. quarts/min.) (1.23 Imp. quarts/min.)		Feeding capacity More than 1,700 cc/min. (1.80 U.S. quarts/min.) (1.50 Imp. quarts/min.)	
Feeding capacity	Cartridge, paper element		Fuel filter Nylon 6 - 150 mesh	
Fuel filter	Down draft, 2 stage 4 barrel		Pressure regulator Type Diaphragm	
Carburetor	Throat diameter		Fuel pressure 200 ~ 260 kpa (28.4 ~ 37.0 lb/in ²)	
Type	Primary 28 mm (1.10 in)		Throttle chamber Type Horizontal - draft (2 stage, 3 barrel)	
Throat diameter	Secondary 34 mm (1.34 in)		Throat diameter Primary 40 mm (1.6 in)	
Primary	Venturi diameter		Secondary 36 mm (1.4 in) X 2	
Secondary	Primary 20 X 13 X 6.5 mm (0.79 X 0.51 X 0.26 in)		Idling speed 800 rpm	
Venturi diameter	Secondary 28 X 10 mm (1.10 X 0.39 in)		Air cleaner element Long life dry	
Primary			Sub-zero starting assist fluid Anti-freeze 90% Water 10%	
Secondary				
	Manual transmission	Automatic transmission		
Main jet			TIGHTENING TORQUE	
Primary	# 92	# 91		
Secondary	# 160	# 160		
Main air bleed				
Primary No. 1	# 70	# 60		
No. 2	# 70	# 70		
Secondary	# 140	# 140		
Slow jet				
Primary	# 46	# 46		
Secondary	# 110	# 110		
Slow air bleed				
Primary No. 1	# 70	# 70		
No. 2	# 170	# 150		
Secondary No. 1	# 160	# 160		
No. 2	# 60	# 60		
Richer jet	# 40	-		
Richer air bleed	# 130	-		
Vacuum jet				
Primary	1.8 mm (0.0709 in)			
Fast idle adjustment	1.0 ~ 1.2 mm (0.039 ~ 0.047 in)			
(Clearance between primary throttle valve and bore when choke knob is fully pulled)				
Float level (from surface of gasket)	16.0 ± 0.5 mm (0.63 ± 0.020 in)			
Float drop (from surface of gasket)	51 ± 0.5 mm (2.0 ± 0.02 in)			
Idling speed				
Manual transmission	750 rpm			
Automatic transmission ("D" range)	750 rpm			
			5. ENGINE ELECTRICAL SYSTEM	
			Battery	
			Type	
			California	
			50 D20R	
			Except for California	
			Manual transmission	
			50D20R, 65D23R	
			Automatic transmission	
			65D23R	
			Capacity (20 hours Rate)	
			55 amp, 65D23R	
			50 amp, 50D20R	
			Voltage	
			12 Volt	
			Terminal ground	
			Negative	
			Specific gravity at 20°C (68°F)	
			50D20R, 65D23R	
			Fully charged	
			1.280	
			Recharged at	
			1.220	
			Distributor	
			Air gap	
			0.5 ~ 0.9 mm (0.020 ~ 0.035 in)	

Centrifugal advance 12A Engine Leading	Starts: 0° at 500 rpm Maximum: 12.5° at 2,063 rpm	Load test Voltage Current 12A Engine 13B Engine Revolution Number of brushers Brush length Wear limit Brush spring pressure Pulley ratio of eccentric shaft and alternator Ignition coil (Leading) Type Primary resistance Ignition coil (Trailing) Type Primary resistance	13.5V	
	Trailing		Starts: 0° at 500 rpm Maximum: 12.5° at 2,063 rpm	More 26 amp. More 21 amp. Less than 1300 rpm 2 16.5 mm (0.650 in) 8 mm (0.315 in) 0.3 ~ 0.44 kg (10.6 ~ 15.5 oz) 1 : 2.08
13B Engine Leading	Starts: 0° at 500 rpm Maximum: 13.75° at 2,000 rpm	Ignition coil (Trailing) Type Primary resistance	LB-84 or FTC-3 0.9 ± 0.09 Ω at 20°C (68°F)	
	Trailing		Starts: 0° at 500 rpm Maximum: 13.75° at 2,000 rpm	LB-84 or FTC-3 0.9 ± 0.09 Ω at 20°C (68°F)
Vacuum advance 12A Engine Leading	Starts: 0° at 100 mm-Hg (3.9 in-Hg) Maximum: 4.5° at -190 mm-Hg (7.5 in-Hg)	Starting motor Capacity Lock test Voltage Current Torque Free running test Voltage Current Speed Number of brushes Brush length Wear limit Standard spring tension Control switch Voltage required to close solenoid contacts Undercutting mica Clearance between armature shaft and bush Armature shaft end play Clearance between pinion and stop collar	Manual transmission	Automatic transmission
	Trailing		Start: 0° at -100 mm-Hg (3.9 in-Hg) Maximum: 15° at -400 mm-Hg (15.7 in-Hg)	1.2 KW 5.0 volt Less than 420 amp. 9.6 N-m (6.9 ft-lb)
13B Engine Leading	Starts: 0° at -100 mm-Hg (3.9 in-Hg) Maximum: 5° at -250 mm-Hg (9.8 in-Hg)	Torque Free running test Voltage Current Speed Number of brushes Brush length Wear limit Standard spring tension Control switch Voltage required to close solenoid contacts Undercutting mica Clearance between armature shaft and bush Armature shaft end play Clearance between pinion and stop collar	11.5 volt Less than 60 amp. More than 6,500 rpm 4 17 mm (0.67 in) 11.5 mm (0.45 in) 1.4 ~ 2.6 kg (49 ~ 92 oz) Solenoid Less than 8 volt 0.5 ~ 0.8 mm (0.020 ~ 0.031 in)	11.5 volt Less than 100 amp. More than 3,500 rpm 4 17 mm (0.67 in) 11.5 mm (0.45 in) 1.4 ~ 2.6 kg (49 ~ 92 oz) Solenoid Less than 8 volt 0.5 ~ 0.8 mm (0.020 ~ 0.031 in)
	Trailing		Start: 0° at -100 mm-Hg (3.9 in-Hg) Maximum: 12.5° -350 mm-Hg (13.8 in-Hg)	11.5 volt Less than 60 amp. More than 6,500 rpm 4 17 mm (0.67 in) 11.5 mm (0.45 in) 1.4 ~ 2.6 kg (49 ~ 92 oz) Solenoid Less than 8 volt 0.5 ~ 0.8 mm (0.020 ~ 0.031 in)
Condenser capacity	0.24 ~ 0.30 μF			
Ignition timing Leading 12A Engine 13B Engine Trailing	0° ATDC 5° ATDC 20° ATDC			
Timing mark location	Eccentric shaft pulley			
Spark plug Type	NGK: BR7EQ14, BR8FQ14 BR9EQ14 NIPPON DENSO W22EDR14 W25EDR14 W27EDR14			
Initial gap	1.4 ± 0.05 mm (0.055 ± 0.002 in)			
Alternator Ground Rated output 12A Engine 13B Engine	Negative 12V 50A 12V 55A			

6. CLUTCH		Clearance between shift rod gate and control lever			
Clutch pedal		Wear limit	0.8 mm (0.0315 in)		
Free play (at pedal pad)	0,6 ~ 3,1 mm (0,0236 ~ 0,1220 in)	Synchronizer ring			
Engagement height (from floor)	More than 75 mm (2,9528 in)	Clearance between synchronizer ring and side of gear when fitted			
Master cylinder		Standard	1.5 mm (0.0591 in)		
Bore	15,87 mm (0.6248 in)	Wear limit	0.8 mm (0.0315 in)		
Clearance between piston and bore		Lubricant			
Standard	0,032 ~ 0,102 mm (0,0013 ~ 0,0040 in)	Above -18°C (0°F)	A.P.I. Service GL-4 or GL-5 SAE90		
Limit	0,15 mm (0.0059 in)	Below -18°C (0°F)	A.P.I. Service GL-4 or GL-5 SAE80W		
Release cylinder		TIGHTENING TORQUE			
Bore	19,05 mm (0.7500 in)		N-m	ft-lb	
Clearance between piston and bore		Plug for interlock pin hole	10 ~ 15	7 ~ 11	
Standard	0,040 ~ 0,125 mm (0,0016 ~ 0,0049 in)	Control lever to control rod end	8 ~ 12	6 ~ 9	
Limit	0,15 mm (0.0059 in)	Shift fork set bolts	12 ~ 16	9 ~ 12	
Clutch disc		Shift rod end	8 ~ 12	6 ~ 9	
Thickness limit	7,0 mm (0.2756 in)	Main shaft lock nut	130 ~ 210	94 ~ 152	
Rivet depth limit	0,3 mm (0.0118 in)	Top switch	25 ~ 35	18 ~ 25	
Lateral run-out limit	1,0 mm (0.0394 in)	Overdrive switch	25 ~ 35	18 ~ 25	
Diaphragm		Back-up light switch	25 ~ 25	18 ~ 25	
Finger out of alignment		Speedometer driven gear	8 ~ 11	6 ~ 8	
Limit	1,0 mm (0.0394 in)	Bearing cover			
Finger groove wear depth		6T bolts	16 ~ 23	12 ~ 17	
Limit	1,0 mm (0.0394 in)	8T bolts	18 ~ 27	13 ~ 20	
TIGHTENING TORQUE		7B. AUTOMATIC TRANSMISSION			
			N-m	ft-lb	
Flywheel		Gear ratio			
Clutch cover		Low	400 ~ 500	2,458	
		Second	18 ~ 27	1,458	
		Third		1,000	
		OD (Fourth)		0,720	
		Reverse		2,181	
		Fluid type		M2C33F (Type F)	
		Fluid capacity		7,5 liters (7,9 U.S. quarts) (6,6 Imp. quarts)	
7A. MANUAL TRANSMISSION		Drive plate run-out			
Gear ratio		Limit		0,5 mm (0.0197 in)	
		Oil pump			
		Side play of inner gear and outer gear			
		Limit		0,08 mm (0.0031 in)	
First	3,622	Clearance between outer gear and crescent			
Second	2,186	Limit		0,25 mm (0.0098 in)	
Third	1,419	Clearance between outer gear and housing			
Fourth	1,000	Limit		0,25 mm (0.0098 in)	
Reverse	3,493	Side clearance between oil seal ring and groove on oil pump cover		0,4 ~ 0,16 mm (0,0016 ~ 0,0063 in)	
Fifth	0,807	Direct clutch			
Oil capacity	2,0 liters (2,1 U.S. quarts) (1,8 Imp. quarts)	Thickness of drive plate			
Main shaft		Limit		1,6 ~ 1,8 mm (0,0630 ~ 0,0709 in)	
Max. permissible run-out	0,03 mm (0.0012 in)	Total clearance measured between retaining plate and snap ring		0,5 ~ 0,8 mm (0,0197 ~ 0,0315 in)	
Clearance between main shaft and gear (or bush)		End play			
Wear limit	0,15 mm (0.0039 in)	OD gear train			
Reverse idle gear		End play		0,25 ~ 0,50 mm (0,0098 ~ 0,0197 in)	
Clearance between reverse idle gear bush and shaft					
Wear limit	0,15 mm (0.0059 in)				
Shift fork and rod					
Clearance between shift fork and clutch sleeve					
Wear limit	0,5 mm (0.0197 in)				

Front clutch Total clearance measured between retaining plate and snap ring End play of front clutch drum Rear clutch Total clearance measured between retaining plate and snap ring Low and reverse brake Total clearance measured between retaining plate and snap ring Gear assembly Total end play Planetary gear side play Limit Engine stall speed	1,6 ~ 1,8 mm (0,0630 ~ 0,0709 in) 0,5 ~ 0,8 mm (0,0197 ~ 0,0315 in) 0,8 ~ 1,5 mm (0,0315 ~ 0,0591 in) 0,8 ~ 1,05 mm (0,0315 ~ 0,413 in) 0,25 ~ 0,50 mm (0,0098 ~ 0,0197 in) 0,8 mm (0,0315 in) 2,400 ~ 2,650 rpm	Governor pressure <table border="1"> <thead> <tr> <th rowspan="2">Driving speed</th> <th colspan="2">Governor pressure</th> </tr> <tr> <th>Kpa</th> <th>lb/in²</th> </tr> </thead> <tbody> <tr> <td>mph</td> <td></td> <td></td> </tr> <tr> <td>20</td> <td>80 ~ 140</td> <td>11 ~ 17</td> </tr> <tr> <td>35</td> <td>150 ~ 230</td> <td>20 ~ 28.4</td> </tr> <tr> <td>55</td> <td>320 ~ 410</td> <td>46 ~ 58</td> </tr> </tbody> </table>	Driving speed	Governor pressure		Kpa	lb/in ²	mph			20	80 ~ 140	11 ~ 17	35	150 ~ 230	20 ~ 28.4	55	320 ~ 410	46 ~ 58																																																								
Driving speed	Governor pressure																																																																										
	Kpa	lb/in ²																																																																									
mph																																																																											
20	80 ~ 140	11 ~ 17																																																																									
35	150 ~ 230	20 ~ 28.4																																																																									
55	320 ~ 410	46 ~ 58																																																																									
Valve body spring Wire diameter Free length	Pressure regulator valve 1st-2nd shift valve 2nd-3rd shift valve 3rd-4th shift valve Throttle back-up valve Solenoid down shift valve 2nd lock valve Throttle relief valve Orifice check valve	11,7 ± 0,2 mm (0,4606 ± 0,0079 in) 6,6 ± 0,2 mm (0,2598 ± 0,0079 in) 6,9 ± 0,2 mm (0,2717 ± 0,0079 in) 7,3 ± 0,2 mm (0,2874 ± 0,0079 in) 7,3 ± 0,2 mm (0,2874 ± 0,0079 in) 5,55 ± 0,2 mm (0,2185 ± 0,0079 in) 5,55 ± 0,2 mm (0,2185 ± 0,0079 in) 6,5 ± 0,2 mm (0,2559 ± 0,0079 in) 5,0 ± 0,2 mm (0,1969 ± 0,0079 in)	43,0 ± 1,0 mm (1,6929 ± 0,0394 in) 32,0 ± 1,0 mm (1,2599 ± 0,0394 in) 41,0 ± 1,0 mm (1,6142 ± 0,0394 in) 25,8 mm (1,0158 in) 31,8 mm (1,2520 in) 22,0 ± 1,0 mm (0,8662 ± 0,0394 in) 33,5 ± 1,0 mm (1,3189 ± 0,0394 in) 26,8 ± 1,0 mm (1,0551 ± 0,0394 in) 15,5 ± 2,0 mm (0,6102 ± 0,0079 in)																																																																								
Shift speed	<table border="1"> <thead> <tr> <th>Throttle condition (Manifold vacuum)</th> <th></th> <th>mph</th> </tr> </thead> <tbody> <tr> <td rowspan="4">Kick-down (0 ~ 100 mm-Hg) (0 ~ 3,94 in-Hg)</td> <td>D1 → D2</td> <td>34 ~ 41</td> </tr> <tr> <td>D2 → D3</td> <td>63 ~ 70</td> </tr> <tr> <td>D3 → D2</td> <td>58 ~ 65</td> </tr> <tr> <td>D2 → D1</td> <td>29 ~ 36</td> </tr> <tr> <td rowspan="3">Half throttle (200 ± 10 mm-Hg) (7,87 ± 0,39 in-Hg)</td> <td>D1 → D2</td> <td>7 ~ 11</td> </tr> <tr> <td>D2 → D3</td> <td>19 ~ 22</td> </tr> <tr> <td>D3 → D4</td> <td>59 ~ 70</td> </tr> <tr> <td>Fully closed throttle</td> <td>D3 → D1</td> <td>7 ~ 11</td> </tr> <tr> <td>Manual 1</td> <td>I2 → I1</td> <td>27 ~ 34</td> </tr> <tr> <td>Lock up on</td> <td>D4</td> <td>42 ~ 48</td> </tr> </tbody> </table>	Throttle condition (Manifold vacuum)		mph	Kick-down (0 ~ 100 mm-Hg) (0 ~ 3,94 in-Hg)	D1 → D2	34 ~ 41	D2 → D3	63 ~ 70	D3 → D2	58 ~ 65	D2 → D1	29 ~ 36	Half throttle (200 ± 10 mm-Hg) (7,87 ± 0,39 in-Hg)	D1 → D2	7 ~ 11	D2 → D3	19 ~ 22	D3 → D4	59 ~ 70	Fully closed throttle	D3 → D1	7 ~ 11	Manual 1	I2 → I1	27 ~ 34	Lock up on	D4	42 ~ 48																																														
Throttle condition (Manifold vacuum)		mph																																																																									
Kick-down (0 ~ 100 mm-Hg) (0 ~ 3,94 in-Hg)	D1 → D2	34 ~ 41																																																																									
	D2 → D3	63 ~ 70																																																																									
	D3 → D2	58 ~ 65																																																																									
	D2 → D1	29 ~ 36																																																																									
Half throttle (200 ± 10 mm-Hg) (7,87 ± 0,39 in-Hg)	D1 → D2	7 ~ 11																																																																									
	D2 → D3	19 ~ 22																																																																									
	D3 → D4	59 ~ 70																																																																									
Fully closed throttle	D3 → D1	7 ~ 11																																																																									
Manual 1	I2 → I1	27 ~ 34																																																																									
Lock up on	D4	42 ~ 48																																																																									
Line pressure	<table border="1"> <thead> <tr> <th rowspan="2">Manual range</th> <th colspan="2">Engine idling condition</th> <th colspan="2">Engine stall condition</th> </tr> <tr> <th>Kpa</th> <th>lb/in²</th> <th>Kpa</th> <th>lb/in²</th> </tr> </thead> <tbody> <tr> <td>R</td> <td>400 ~ 700</td> <td>57 ~ 100</td> <td>1600 ~ 1900</td> <td>228 ~ 270</td> </tr> <tr> <td>D</td> <td>300 ~ 400</td> <td>43 ~ 57</td> <td>900 ~ 1100</td> <td>128 ~ 156</td> </tr> <tr> <td>2</td> <td>800 ~ 1200</td> <td>114 ~ 171</td> <td>800 ~ 1200</td> <td>114 ~ 171</td> </tr> <tr> <td>1</td> <td>300 ~ 400</td> <td>43 ~ 57</td> <td>900 ~ 1100</td> <td>128 ~ 156</td> </tr> </tbody> </table>	Manual range	Engine idling condition		Engine stall condition		Kpa	lb/in ²	Kpa	lb/in ²	R	400 ~ 700	57 ~ 100	1600 ~ 1900	228 ~ 270	D	300 ~ 400	43 ~ 57	900 ~ 1100	128 ~ 156	2	800 ~ 1200	114 ~ 171	800 ~ 1200	114 ~ 171	1	300 ~ 400	43 ~ 57	900 ~ 1100	128 ~ 156																																													
Manual range	Engine idling condition		Engine stall condition																																																																								
	Kpa	lb/in ²	Kpa	lb/in ²																																																																							
R	400 ~ 700	57 ~ 100	1600 ~ 1900	228 ~ 270																																																																							
D	300 ~ 400	43 ~ 57	900 ~ 1100	128 ~ 156																																																																							
2	800 ~ 1200	114 ~ 171	800 ~ 1200	114 ~ 171																																																																							
1	300 ~ 400	43 ~ 57	900 ~ 1100	128 ~ 156																																																																							
		TIGHTENING TORQUE	<table border="1"> <thead> <tr> <th></th> <th>N-m</th> <th>ft-lb</th> </tr> </thead> <tbody> <tr> <td>Drive plate to converter weight</td> <td>83 ~ 95</td> <td>60 ~ 69</td> </tr> <tr> <td>Drive plate to torque converter</td> <td>35 ~ 50</td> <td>25 ~ 36</td> </tr> <tr> <td>Converter housing to engine</td> <td>32 ~ 47</td> <td>23 ~ 34</td> </tr> <tr> <td>Converter housing to transmission case</td> <td>45 ~ 55</td> <td>33 ~ 40</td> </tr> <tr> <td>Extension housing to transmission case</td> <td>20 ~ 25</td> <td>14 ~ 18</td> </tr> <tr> <td>Oil pan</td> <td>6 ~ 8</td> <td>4.3 ~ 5.8</td> </tr> <tr> <td>Piston stem (when adjusting band brake)</td> <td>12 ~ 15</td> <td>9 ~ 11</td> </tr> <tr> <td>Piston stem lock nut</td> <td>15 ~ 40</td> <td>11 ~ 29</td> </tr> <tr> <td>Servo piston retainer</td> <td>7 ~ 9</td> <td>5 ~ 7</td> </tr> <tr> <td>One-way clutch inner race</td> <td>13 ~ 18</td> <td>9 ~ 13</td> </tr> <tr> <td>Control valve body to transmission case</td> <td>5,5 ~ 7,5</td> <td>4,0 ~ 5,4</td> </tr> <tr> <td>Lower valve body to upper valve body</td> <td>2,5 ~ 3,5</td> <td>1,8 ~ 2,5</td> </tr> <tr> <td>Side plate to control valve body</td> <td>2,5 ~ 3,5</td> <td>1,8 ~ 2,5</td> </tr> <tr> <td>Reamer bolt of control valve body</td> <td>5 ~ 7</td> <td>3,6 ~ 5,1</td> </tr> <tr> <td>Oil strainer</td> <td>3 ~ 4</td> <td>2,2 ~ 2,9</td> </tr> <tr> <td>Governor valve body to oil distributor</td> <td>5 ~ 7</td> <td>3,6 ~ 5,1</td> </tr> <tr> <td>Oil pump cover</td> <td>6 ~ 9</td> <td>4,3 ~ 6,5</td> </tr> <tr> <td>Drum support</td> <td>6 ~ 9</td> <td>4,3 ~ 6,5</td> </tr> <tr> <td>Inhibitor switch</td> <td>5 ~ 7</td> <td>3,6 ~ 5,1</td> </tr> <tr> <td>Manual shaft lock nut</td> <td>30 ~ 40</td> <td>22 ~ 29</td> </tr> <tr> <td>Oil cooler pipe set bolt</td> <td>24 ~ 36</td> <td>17 ~ 26</td> </tr> <tr> <td>Oil pressure test plug</td> <td>5 ~ 10</td> <td>3,6 ~ 7,2</td> </tr> <tr> <td>Actuator for parking rod to extension housing</td> <td>8 ~ 11</td> <td>5,8 ~ 8,0</td> </tr> </tbody> </table>		N-m	ft-lb	Drive plate to converter weight	83 ~ 95	60 ~ 69	Drive plate to torque converter	35 ~ 50	25 ~ 36	Converter housing to engine	32 ~ 47	23 ~ 34	Converter housing to transmission case	45 ~ 55	33 ~ 40	Extension housing to transmission case	20 ~ 25	14 ~ 18	Oil pan	6 ~ 8	4.3 ~ 5.8	Piston stem (when adjusting band brake)	12 ~ 15	9 ~ 11	Piston stem lock nut	15 ~ 40	11 ~ 29	Servo piston retainer	7 ~ 9	5 ~ 7	One-way clutch inner race	13 ~ 18	9 ~ 13	Control valve body to transmission case	5,5 ~ 7,5	4,0 ~ 5,4	Lower valve body to upper valve body	2,5 ~ 3,5	1,8 ~ 2,5	Side plate to control valve body	2,5 ~ 3,5	1,8 ~ 2,5	Reamer bolt of control valve body	5 ~ 7	3,6 ~ 5,1	Oil strainer	3 ~ 4	2,2 ~ 2,9	Governor valve body to oil distributor	5 ~ 7	3,6 ~ 5,1	Oil pump cover	6 ~ 9	4,3 ~ 6,5	Drum support	6 ~ 9	4,3 ~ 6,5	Inhibitor switch	5 ~ 7	3,6 ~ 5,1	Manual shaft lock nut	30 ~ 40	22 ~ 29	Oil cooler pipe set bolt	24 ~ 36	17 ~ 26	Oil pressure test plug	5 ~ 10	3,6 ~ 7,2	Actuator for parking rod to extension housing	8 ~ 11	5,8 ~ 8,0
	N-m	ft-lb																																																																									
Drive plate to converter weight	83 ~ 95	60 ~ 69																																																																									
Drive plate to torque converter	35 ~ 50	25 ~ 36																																																																									
Converter housing to engine	32 ~ 47	23 ~ 34																																																																									
Converter housing to transmission case	45 ~ 55	33 ~ 40																																																																									
Extension housing to transmission case	20 ~ 25	14 ~ 18																																																																									
Oil pan	6 ~ 8	4.3 ~ 5.8																																																																									
Piston stem (when adjusting band brake)	12 ~ 15	9 ~ 11																																																																									
Piston stem lock nut	15 ~ 40	11 ~ 29																																																																									
Servo piston retainer	7 ~ 9	5 ~ 7																																																																									
One-way clutch inner race	13 ~ 18	9 ~ 13																																																																									
Control valve body to transmission case	5,5 ~ 7,5	4,0 ~ 5,4																																																																									
Lower valve body to upper valve body	2,5 ~ 3,5	1,8 ~ 2,5																																																																									
Side plate to control valve body	2,5 ~ 3,5	1,8 ~ 2,5																																																																									
Reamer bolt of control valve body	5 ~ 7	3,6 ~ 5,1																																																																									
Oil strainer	3 ~ 4	2,2 ~ 2,9																																																																									
Governor valve body to oil distributor	5 ~ 7	3,6 ~ 5,1																																																																									
Oil pump cover	6 ~ 9	4,3 ~ 6,5																																																																									
Drum support	6 ~ 9	4,3 ~ 6,5																																																																									
Inhibitor switch	5 ~ 7	3,6 ~ 5,1																																																																									
Manual shaft lock nut	30 ~ 40	22 ~ 29																																																																									
Oil cooler pipe set bolt	24 ~ 36	17 ~ 26																																																																									
Oil pressure test plug	5 ~ 10	3,6 ~ 7,2																																																																									
Actuator for parking rod to extension housing	8 ~ 11	5,8 ~ 8,0																																																																									

8. PROPELLER SHAFT		Backlash between rack and sector gear	Adjust to 0 mm
Max. permissible runout	0.4 mm (0.016 in)	Worm bearing preload	0.2 ~ 0.5 N-m (1.7 ~ 4.3 in-lb)
Max. permissible unbalance at 4,000 rpm		Without sector shaft and column bush	0.6 ~ 1.2 N-m (5.2 ~ 10.4 in-lb)
At front	15 cm-gr (0.21 in-oz)	With sector shaft and column bush	
At rear	15 cm-gr (0.21 in-oz)	Clearance between sector shaft and housing bush	0.1 mm (0.004 in)
Universal joint		Wear limit	0 ~ 0.1 mm (0 ~ 0.004 in)
Journal swinging torque	0.3 ~ 0.8 N-m (2.6 ~ 6.9 in-lb)	End clearance of adjusting screw and sector shaft	A.P.I. Service GL-4 SAE90
TIGHTENING TORQUE		Lubricant	290 cc (0.31 U.S. quarts) (0.26 Imp. quarts)
		Oil capacity	
	N-m	ft-lb	
Yoke to rear axle companion flange	35 ~ 38	25 ~ 27	Max. Wheel angle on full lock
			Wheel on inside of curve
			Wheel on outside of curve
			Idler arm revolving torque
9. REAR AXLE		Kuckle arm ball stud revolving torque	More than 0.4 kg (14 oz)
Reduction ratio		Steering geometry	
12A engine powered vehicle	3.909	King-pin inclination	
13B engine powered vehicle	4.076	13 inch tire vehicles	10°44'
Backlash of ring gear and pinion	0.09 ~ 0.11 mm (0.0035 ~ 0.0043 in)	14 inch tire vehicles	11°20'
Pinion bearing preload (Without pinion oil seal)	0.9 ~ 1.4 N-m (7.8 ~ 12.2 in-lb)	Camber	
Differential side bearing preload (Without pinion)	0.6 ~ 2.1 N-m (5.2 ~ 18.2 in-lb)	13 inch tire vehicles	1°00' ± 30'
Backlash of side gear and pinion gear	0 ~ 0.1 mm (0 ~ 0.0039 in)	14 inch tire vehicles	0°35' ± 30'
Rear wheel bearing end play	0 ~ 0.1 mm (0 ~ 0.0039 in)	Max. permissible difference in camber between sides	±30'
Lubricant		Camber offset	38 mm (1.50 in)
Standard diff.		Caster	Right-hand side 4°10' ± 30'
Above -18°C (0°F)	A.P.I. Service GL-5 SAE90	Max. permissible difference in caster between sides	Left-hand side 3°40' ± 30'
Below -18°C (0°F)	A.P.I. Service GL-5 SAE80W	Caster trail	±30'
Limited slip diff.	A.P.I. Service GL-5 SAE90 (Special Lubricant For Limited Slip Differentials)	Toe-in	20 mm (0.79 in)
Oil capacity			0 ~ 6 mm (0 ~ 0.24 in)
Standard diff.	1.2 liters (1.3 U.S. quarts) (1.1 Imp. quarts)	10B. POWER STEERING	
Limited slip diff.	1.6 liters (1.7 U.S. quarts) (1.4 Imp. quarts)	Type	Integral ball nut
"L" (Case spread)	185,428 ~ 185,500 mm (7,3004 ~ 7,3033 in)	Reduction ratio	15.83 : 1
TIGHTENING TORQUE		Free play of steering wheel (Turning direction)	
		Standard	5 ~ 20 mm (0.2 ~ 0.8 in)
	N-m	Limit	40 mm (1.57 in)
	ft-lb	Backlash between rack and sector gear	
Ring gear	70 ~ 85	Clearance between gear housing and ball nut	0.15 mm (0.0059 in)
Differential side bearing caps	38 ~ 53	Limit	
Companion flange to pinion	13 ~ 18	Clearance between gear housing and sector shaft	0.10 mm (0.0039 in)
10A. MANUAL STEERING		Limit	
Reduction ratio	17.0 ~ 20.0 : 1	Worm bearing preload	0.4 ~ 0.7 N-m (3.5 ~ 6.1 in-lb)
Free play of steering wheel (Turning direction)		Before adjusting backlash	0.5 ~ 0.9 N-m (4.3 ~ 7.8 in-lb)
Standard	5 ~ 20 mm (0.2 ~ 0.8 in)	After adjusting backlash	
Limit	40 mm (1.57 in)	Max. wheel angle on full lock	
		Wheel on inside of curve	39°14' ± 2°
		Wheel on outside of curve	32°14' ± 2°
		Oil	ATF Type F (M2C33-F)

TIGHTENING TORQUE			Standard	0,040 ~ 0.125 mm (0,0016 ~ 0,0049 in)
	N-m	ft-lb	Limit	0,15 mm (0,006 in)
Steering wheel nut	40 ~ 50	29 ~ 36	Remaining pressure	50 ~ 100 kpa (7,1 ~ 14,2 lb/in ²)
Steering gear housing to frame	44 ~ 55	32 ~ 40	Clearance between drum and lining	0,1 ~ 0,15 mm (0,004 ~ 0,006 in)
Pitman arm to sector shaft	150 ~ 180	108 ~ 130	Parking brake Lever travel	6 ~ 8 notches at 10 kg (22 lb)
Idler arm bracket to frame	44 ~ 55	32 ~ 40	TIGHTENING TORQUE	
Idler arm to center link	25 ~ 35	18 ~ 25		
Pitman arm to center link	30 ~ 45	22 ~ 33		
Tie-rod to center link	30 ~ 45	22 ~ 33		
Tie-rod to knuckle arm	30 ~ 45	22 ~ 33		
Tie-rod lock nut	70 ~ 80	51 ~ 58		
Steering gear box end cover lock nut	230 ~ 260	166 ~ 188		
11. BRAKING SYSTEM				
Brake pedal free travel	7 ~ 9 mm			
Before power brake piston operates	(0,28 ~ 0,35 in)			
Brake pedal height (from floor)	190 ~ 195 mm (7,48 ~ 7,68 in)			
Master cylinder Bore	20,64 mm (0,813 in)			
Clearance between piston and bore				
Standard	0,040 ~ 0,125 mm (0,0016 ~ 0,0049 in)			
Wear limit	0,15 mm (0,006 in)			
Power brake unit Clearance between piston and push rod	0,1 ~ 0,5 mm (0,004 ~ 0,020 in)			
Front disc brake Thickness of brake disc				
Standard	18 mm (0,7087 in)			
Limit	17 mm (0,6693 in)			
Max. allowable lateral run-out of brake disc	0,1 mm (0,0039 in)			
Thickness of lining				
Standard	9 mm (0,3543 in)			
Thickness limit	1 mm (0,039 in)			
Caliper cylinder bore	50,80 mm (2,0 in)			
Rear disc brake Thickness of brake disc				
Standard	10 mm (0,3937 in) ...Solid 22 mm (0,866 in) ...Ventilated			
Limit	9 mm (0,3543 in) ...Solid 20 mm (0,787 in) ...Ventilated			
Max. allowable lateral run-out of brake disc	10 mm (0,3937 in) 9 mm (0,3543 in)			
Thickness of lining				
Standard	0,1 mm (0,0039 in)			
Thickness limit				
Caliper cylinder bore	6 mm (0,2362 in) 1 mm (0,039 in)			
Rear drum brake Drum diameter	34,93 mm (1,3752 in)			
Standard				
Limit				
Thickness of lining	200 mm (7,8741 in) 201 mm (7,9135 in)			
Standard				
Thickness limit				
Wheel cylinder bore	4,0 mm (0,1575 in) 1,0 mm (0,039 in)			
Clearance between piston and bore	19,05 mm (0,750 in)			
12. WHEELS AND TIRES				
Wheel disc				
Front	5-J x 13 WDC 5½-JJ x 13 WDC (Aluminum)			
Rear	5-J x 13 WDC 5½-JJ x 13 WDC (Aluminum)			
Front	5½-JJ x 14 WDC			
Rear	5½JJ x 14 WDC			
Temporary spare tire	4 - T x 15			
Run-out limit				
Radial	1,0 mm (0,04 in) 0,5 mm (0,020 in) Aluminum			
Lateral	1,0 mm (0,04 in) 0,5 mm (0,020 in) Aluminum			
Tire				
Front	185/70 HR 13 165HR 13 205/60 VR 14			
Rear	185/70 HR 13 165HR 13 205/60 VR 14			
Temporary spare tire	T135/70 D 15			
Inflation pressure				
Front	190 kpa (27 psi) 200 kpa (28 psi) ... 14 in only			
Rear	190 kpa (27 psi) 200 kpa (28 psi) ... 14 in only			
Temporary spare tire	420 kpa (60 psi)			
Run-out limit (with wheel disc)				
Radial	2,5 mm (0,098 in)			
Lateral	3,0 mm (0,118 in)			
Front wheel bearing preload (at wheel set bolt)	0,45 ~ 0,65 kg (0,99 ~ 1,43 lb)			
TIGHTENING TORQUE				
	N-m	ft-lb		
Wheel bolts	90 ~ 120	65 ~ 87		

13. SUSPENSION			15. BODY ELECTRICAL SYSTEM		
Front coil spring	2.16 ± 0.15 kg/mm		Item	Specification (W)	
Spring constant					
Free length			Headlights		
Standard	Left	334.5 mm (13.17 in)	Halogen headlights	50/60 50, 40/55 (Normal)	
	Right	32.5 mm (12.80 in)	Rear side marker lights	3.8	
Front shock absorber			Turn-signal lights	27	
Fluid capacity	225 ⁺⁵ / ₋₀ cc (0.23 ^{+0.05} / ₋₀ U.S. quarts)		Front parking lights	8	
Rear coil spring			Rear turn signal lights	27	
Spring constant	1.8 ± 0.13 kg/mm		Tail lights	8	
Free length			Stop lights	27	
Standard	323.5 mm (12.74 in)		Back-up lights	27	
TIGHTENING TORQUE			License plate lights	6	
			Indicator and warning lights		
Suspension arm to cross member	N-m	ft-lb	Interior lights	10	
	40 ~ 55	29 ~ 40	Map lights	6	
Knuckle arm to shock absorber	64 ~ 95	46 ~ 69	Luggage compartment lights	5	
Suspension arm ball joint to knuckle arm	60 ~ 80	43 ~ 58	Turn signals	3.4	
Front shock absorber piston rod to mounting block	65 ~ 82	47 ~ 59	High beam	3.4	
Seal cap nut	50 ~ 60	36 ~ 43	Oil pressure	1.4	
Tension rod to lower suspension arm	55 ~ 69	40 ~ 50	Alternator	1.4	
Tension rod to bracket	110 ~ 150	80 ~ 108	Stop lights	1.4	
Tension rod bracket to frame	76 ~ 107	55 ~ 77	Brake	1.4	
Stabilizer bar to suspension lower arm	12 ~ 18	9 ~ 13	Parking brake	1.4	
Front stabilizer support plate	38 ~ 47	27 ~ 34	Fuel	3.4	
Shock absorber to axle housing	65 ~ 82	47 ~ 59	Hazard	3.4	
Upper link to axle housing	77 ~ 105	56 ~ 76	Washer level	1.4	
Upper link to frame	77 ~ 105	56 ~ 76	Seat belt	1.4	
Lower link to axle housing	77 ~ 105	56 ~ 76	Illumination lights		
Lower link to frame	77 ~ 105	56 ~ 76	Automatic selector lever	3.4	
Shock absorber upper	13 ~ 25	9 ~ 18	Heater	3.4	
Watt link bracket	77 ~ 105	56 ~ 76	Meter	3.4 & 1.4	
Watt link to axle housing	65 ~ 82	47 ~ 59	Cigarette lighter	3.4	
Watt link to bracket	65 ~ 82	47 ~ 59	Radio	3.4	
Rear stabilizer support plate	32 ~ 47	23 ~ 34	Rear window defroster	1.4	
Stabilizer lock nut	10 ~ 16	7 ~ 12	TIGHTENING TORQUE		
			Unless otherwise specified		
			6T		
			6 mm bolt/nut	7 ~ 10	5 ~ 7
			8 mm bolt/nut	16 ~ 23	12 ~ 17
			10 mm bolt/nut	32 ~ 47	23 ~ 34
			12 mm bolt/nut	56 ~ 82	41 ~ 59
			14 mm bolt/nut	77 ~ 105	56 ~ 76
			8T		
			6 mm bolt/nut	8 ~ 12	6 ~ 9
			8 mm bolt/nut	18 ~ 17	13 ~ 20
			10 mm bolt/nut	37 ~ 55	27 ~ 40
			12 mm bolt/nut	64 ~ 95	46 ~ 69
			14 mm bolt/nut	104 ~ 140	75 ~ 101